

YE-218B 双缸鞋面定型机 Instep Moulding Machine

1. 本机适用于女高跟鞋和男女靴类在结帮之前对鞋面的定型作业。
2. 胶模采用耐磨耐热硅胶；外铝模温度可达 200°C。
3. 定型后，内衫贴全紧密，不起皱，不变形，不起泡，且可减少破损。
4. 可及时造型打样，减少样品开发时间，降低成本，并能更好的满足客户要求。
5. 鞋背的准确定型更易于前帮机的操作，从而可提高产量。
6. 下模可随意调节而达到不同需要的距度，更贴楦。
7. 双工位设计，更能快速提高生产量。

1. This aircraft is suitable for the female high-heeled shoes and the male woman's boot class before forming a group to instep moulding work.
2. The jelly mold uses the wear-resisting heat-resisting silica gel; Outside the aluminum mold temperature may reach 200°C.
3. After the moulding, in the unlined upper garment pastes entire close, the corrugation, does not distort, does not bubble, and may reduce the breakage.
4. But the prompt moduling pulls, reduces the sample development time, reduces the cost, and can the better satisfied customer request.
5. The shoes back's accurate stereotypical change raises the Productivity.
6. The stamping die may adjust at will achieves the different need the clearance, pastes the shoetree.
7. The double location design, can enhance the productivity fast.

| 机械尺寸 Dimensions | 电压 Voltage | 重量 Weight | 电热系统 Heating System | 空气源 Air pressure |
|-----------------|------------|-----------|---------------------|------------------|
| 1120X600X1700mm | 220V/50HZ | 350kg | 1.2KW | 0.6MPa |



远益®
UANYI

YUANYI SHOE MAKING MACHINE

远益鞋机



YE-218B 双缸鞋面定型机
YE-218B Upper Moulding Machine

since
96
专心 专业 创新
www.cneaga.com